



## OAK ERVE

The fawn brown and earthy tones found in this 3-strip oak floor from the Tres Collection are dotted with darker knots for a lively and rustic expression.

### PRODUCT DETAILS

|                       |                                             |
|-----------------------|---------------------------------------------|
| Article Number        | 133NCDEK15KW 0                              |
| EANCode               | 7393969034234                               |
| Surface treatment     | Matt lacquer                                |
| Dimensions            | 2423 x 200 x 13 mm                          |
| Weight per Package x  | 24.5 kg                                     |
| Area per Package (m²) | 3.4                                         |
| AreaPerPalletM2       | 170                                         |
| Package info          | Packages may contain start and stop boards. |

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

### COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

### FACTS

|                      |                     |
|----------------------|---------------------|
| Wood Species         | Oak                 |
| Board                | 3-strip             |
| Grading              | Lively              |
| Range                | Kährs Avanti        |
| Collection           | Tres Collection     |
| Resandable           | 2-3 times           |
| Natural/Stained      | Natural             |
| Brinell Value        | 3,7                 |
| Joint                | Woodloc® 5S         |
| Floor heating        | Yes                 |
| Warranty             | 20 years            |
| Wear-layer material  | Hardwood            |
| Wear-layer thickness | 2.6 mm              |
| Core material        | Pine/Spruce lamella |
| Thickness            | 13 mm               |

### TECHNICAL PROPERTIES

|                             |             |
|-----------------------------|-------------|
| TestMoistureContent         | 7%±2%       |
| TestMinimunMeanDensity      | >500 kg/m³  |
| TestReactionToFire          | Dfl-s1      |
| TestFormaldehydeEmission    | E1          |
| TestContentPCP              | ≤ 5 x 10-6n |
| TestBreakingStrength        | NPD         |
| TestThermalConductivity     | 0,14 W/mK   |
| TestThermalResistanceRValue | .09 (m2K/W) |
| TestBiologDurability        | Class 1     |
| TestCarb2                   | Compliant   |



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*