



SERENGETI CLA 200

The warm, brown tones of Serengeti characterize the design of the Aware Serengeti floor. The colour of the floor creates a calm homely but authentic feeling. The design includes nature features like knots and cracks for an authentic look.

PRODUCT DETAILS

Article Number	LTAWAW1115
Dimensions	200 x 1815 mm
Weight per Package	15.84 kg
Area per Package	2.17 m ²
Area per pallet	104.16 m ²
Construction	HDF Click

FACTS

Design	Wood design
Application area	Commercial, Residential
Range	Luxury Tiles
Collection	Aware Collection
Floor heating	Yes
Warranty	30 years residential/15 years commercial
Thickness	9 mm
Installation method	Floating

TECHNICAL PROPERTIES

Product specification	EN 16511	
Application	EN ISO 10874	CL 23/33
Abrasion resistance class	EN 15468 AC5	
Effect of furniture leg	EN ISO 16581	No visible damage/Change
Impact resistance	>1800 mm	
Content of specific dangerous substances	Compliant, not actively added	
Emission of formaldehyde	E1	
Resistance against staining	EN 438-2	Grade 4-5
Reaction To Fire	EN13501-1	Cfl-s1
Thermal Conductivity	EN12664	0.118 W/(m*K)
CARB2	Compliant	

DETAIL DESCRIPTION

A durable, bio-based, natural luxury tiles floor, designed to withstand family-life as well as wear and tear of commercial applications (usage class 33), with the style, beauty and feel of a wooden floor. Based on reclaimed, recycled, and natural fibers. With a water resistant surface, elastic properties for high comfort and good acoustic properties with an integrated cork backing.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

Residual indentation EN ISO 24343-1		$\bar{x}$ 0.08 mm (with underlayer)	
Dimensional stability	EN ISO 23999	< 0.15 % (80 °C/6 h)	
Slip resistance	EN 13893	DS	
Slip resistance	DIN 51130	R10	
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	
Scratch resistance	EN16094	MSR-A2	
Effect of castor chair	EN 425	Suitable	
Impact sound reduction	EN ISO 10140	17 ΔLw dB (Integrated cork underlayment)	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



27.06.2023

AB GUSTAF KÄHR | www.kahrs.com | © Kährs 2023

Other products in this collection



Serengeti CLA 200



Rocky CLA 200



Yellowstone CLA 200



Smoky CLA 200



Grand Canyon CLA 200



Kappadokien CLA 200



Bwindi CLA 200



Jasper CLA 200



Yosemite CLA 200

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.