



OAK URSUS

Oak Ursus explores oak's darker, more dramatic registers. Intensive brushing enhances the grain's natural topography, creating a textured interplay of highlights and lowlights beneath the deep oil treatment. Knots and larger cracks are meticulously hand-repaired, preserving character while keeping the visual language refined. The 4-sided micro-bevel frames each plank with a soft contour, adding structure to the dark, immersive colorway.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	131274220 / 7393969306898
Design / Wood Species	Plank / Oak
Surface treatment /	Oil / Stained
Natural/Stained	
Design features	Microbevelled 4-sided, Brushed
Width x Length x Thickness	187 x 2266 x 13 mm
Weight per package / per	24 kg / 7.19 kg
m2	
Area per package / per	3.39 m² / 118.65 m²
pallet	
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 2.6 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce
Backside material	Spruce

PRODUCT DETAILS		
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9	
LRV / LRV Std1 / LRV Std2	10 / 0.9 / 1.8	
Warranty	20 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

All naturally occurring wood color variations are allowed, ranging from light to dark brown tones. Sapwood may be present. The product features very large sound and black knots, as well as natural cracks. Knot holes and cracks are repaired with a dark filler, and larger openings may be plugged with knot inserts.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.


Other products in this collection



OAK URSUS



OAK LARUS



OAK OVIS



OAK LYNX OILED



OAK LYNX ULTRA MATT