



OAK TVETA

The rich, coffee stain on this single-strip oak floor from the Småland Collection allows the fully smoked, charcoal nuances in the wood to seep through, resulting in a very rustic expression. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

PRODUCT DETAILS

| | |
|------------------------------|---|
| Article Number | 151NDSEK04KW240 |
| EANCode | 7393969039055 |
| Surface treatment | Oil This floor should be oiled immediately after installation. |
| Design features | Bevelled 4-sided, Brushed, Light smoked, Handscraped, Saw marks |
| Dimensions | 2420 x 187 x 15 mm |
| Weight per Package x | 22 kg |
| Area per Package (m²) | 2.7 |
| AreaPerPalletM2 | 122.4 |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Board | 1-strip |
| Grading | Expressive |
| Range | Kährs Supreme |
| Collection | Småland Collection |
| Resandable | 2-4 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3.5 mm |
| Core material | Pine/Spruce lamella |
| Thickness | 15 mm |
| Surface Colour | Shadow Brown |

TECHNICAL PROPERTIES

| | |
|------------------------------------|-------------|
| TestMoistureContent | 7%±2% |
| TestMinimunMeanDensity | >500 kg/m³ |
| TestReactionToFire | Dfl-s1 |
| TestFormaldehydeEmission | E1 |
| TestContentPCP | ≤ 5 x 10-6n |
| TestBreakingStrength | NPD |
| TestThermalConductivity | 0,14 W/mK |
| TestThermalResistanceRValue | .11 (m2K/W) |
| TestBiologDurability | Class 1 |
| TestCarb2 | Compliant |



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.