



## OAK SKY

The semi-transparent white stain on this single-strip oak floor from the Lux Collection balances the light and dark contrasts in the wood, allowing the subtle warm oak tones to softly filter through. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

### PRODUCT DETAILS

<b>Article Number</b>	151N8AEKB4KW240
<b>EANCode</b>	7393969044189
<b>Surface treatment</b>	Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles.
<b>Design features</b>	Microbevelled 4-sided, Brushed
<b>Dimensions</b>	2420 x 187 x 15 mm
<b>Weight per Package x</b>	22 kg
<b>Area per Package (m<sup>2</sup>)</b>	2.7
<b>AreaPerPalletM2</b>	122.4
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Lively
<b>Range</b>	Kährs Original
<b>Collection</b>	Lux Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	3.5 mm
<b>Core material</b>	Pine/Spruce/Alder
<b>Thickness</b>	15 mm
<b>Surface Colour</b>	White

### TECHNICAL PROPERTIES

<b>TestMoistureContent</b>	7%±2%
<b>TestMinimunMeanDensity</b>	>500 kg/m <sup>3</sup>
<b>TestReactionToFire</b>	Dfl-s1
<b>TestFormaldehydeEmission</b>	E1
<b>TestContentPCP</b>	≤ 5 x 10 <sup>-6</sup> n
<b>TestBreakingStrength</b>	NPD
<b>TestThermalConductivity</b>	0,14 W/mK
<b>TestThermalResistanceRValue</b>	.11 (m <sup>2</sup> K/W)
<b>TestBiologDurability</b>	Class 1
<b>TestCarb2</b>	Compliant



**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*