



## OAK NOUVEAU RICH

The saturated amber hues enhance the organic grain detailing found in this single-strip oak floor from the Classic Nouveau Collection. Knots and cracks lightly pepper the boards, resulting in a lively yet subdued expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

### PRODUCT DETAILS

<b>Article Number</b>	151N8AEKQ1KW240
<b>EANCode</b>	7393969041737
<b>Surface treatment</b>	Matt lacquer
<b>Design features</b>	Brushed, Microbevelled 4-sided
<b>Dimensions</b>	2420 x 187 x 15 mm
<b>Weight per Package x</b>	22 kg
<b>Area per Package (m<sup>2</sup>)</b>	2.7
<b>AreaPerPalletM2</b>	122.4
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Lively
<b>Range</b>	Kährs Original
<b>Collection</b>	Classic Nouveau Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	3.5 mm
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	15 mm
<b>Surface Colour</b>	Warm brown

### TECHNICAL PROPERTIES

<b>TestMoistureContent</b>	7%±2%
<b>TestMinimunMeanDensity</b>	>500 kg/m <sup>3</sup>
<b>TestReactionToFire</b>	Dfl-s1
<b>TestFormaldehydeEmission</b>	E1
<b>TestContentPCP</b>	≤ 5 x 10 <sup>-6</sup> n
<b>TestBreakingStrength</b>	NPD
<b>TestThermalConductivity</b>	0,14 W/mK
<b>TestThermalResistanceRValue</b>	.11 (m <sup>2</sup> K/W)
<b>TestBiologDurability</b>	Class 1
<b>TestCarb2</b>	Compliant



**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*